


» CP930 «



3U Fast Ethernet Switch

» Fast

Five Fast Ethernet Ports with a data throughput of 1400 Mbps

» Versatile


Versatile design for use in CompactPCI, VME, standard PC or customer specific solutions


» Robust

Robust and suited for harsh environments

Designed for operation in industrial automation applications, the CP930 is a rugged 5-port fast ethernet switch that can be used also in an extended temperature range of -40 to +85°C.

CP930 supports 10Mbit/s and 100Mbit/s Fast Ethernet with RJ45 connectors; each of the five ports with two status LED's. **CP930-FX** offers four RJ45 connectors and one fiber optical port with a 1300 nm MTRJ connector.





Ordering Information Article Order-No. Description CP930 26304 5-port Fast Ethernet switch with 5x RJ45 to the front CP930-E2 26307 5-port Fast Ethernet switch with 5x RJ45 to the front, -40 °C / +85 °C temperature range CP930-FX 26305 5-port Fast Ethernet switch with 4x RJ45 and 1x MT-RJ (1300 nm) to the front

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1 85386 Eching/Munich Germany

Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898 info@us.kontron.com

Asia Pacific

17 Building,Block #1,ABP. 188 Southern West 4th Ring Road Beijing 100070, P.R.China

Tel.: + 86 10 63751188 Fax: + 86 10 83682438 info@kontron.cn

