

Type 39C, 3U - 19" Rackmount/Desktop, Horizontal



FEATURES

- 19" Rackmount fully compliant to IEEE 1101.10/11
- 3U x 443mm x 300mm (H x W x D)
- 3, 4, 5 or 6-slot, PICMG: 2.0, 2.16, EXP.0 backplanes (H.110 optional)
- Cooling side to side
- Advanced EMC shielding to meet CE, FCC Class A and NEBS
- PSU inputs (90 - 264 VAC, 48 VDC)
- Wide range of PSU options: fix mount, plug in, N+1
- Shelf Management: PICMG 2.9, IPMI (optional)
- Ready to run - turnkey solution

SCOPE OF SUPPLY

High quality platform consisting of black painted sheet steel enclosure, high performance PICMG 2.0, 2.16, EXP.0 backplane, power supply, cooling system and AC/DC power components. Assembled, wired and tested prior to shipment.

ORDERING INFORMATION

DESCRIPTION	ORDER NUMBER
<ul style="list-style-type: none">• 3U H x 443mm W x 360mm D• 6 slot, 6U x 160mm, front• 6 slot, 6U x 80mm, rear I/O• 6 slot BP, (PICMG 2.0, wo/H.110)• No device mounting• 3 x 45 CFM fans, side to side• 2 x 200W, PSU - 3U Plug removable	39C06CC138Y3HP2X

Coming Soon

Front View




Side View



Rear View

ENVIRONMENTAL SPECIFICATIONS

	Operating	Storage/Transit
Temperature:	0°C to +50°C	-20°C to +70°C
Altitude:	6000 ft. (1,829m)	50,000 ft. (15,240m)
Humidity:	5% to 95% Non condensing	5% to 95% Non condensing
Shock:	10 G's @ 11ms	15 G's @ 11ms (per ASTM 0775)
Vibration:	1.0 G's @ 10 to 330 Hz	1.2 G's @ 5 to 330 Hz
Agencies:	Designed to meet UL 1950, FCC, A, B, CE	

CUSTOM CONFIGURATIONS

39C     38Y    

  Backplane Configuration

00-21: Single
02 = 2 slot

 Bare Board

A = 6U Eco, ATX, (RSS)
B = 3U Rev. 2.0
C = 6U H110
D = 6U (LSS)
E = 2.16, 1 x FS (no H.110)
F = 2.16, 2 x FS (no H.110)
H = 2.16, 2 x FS (w/ H.110)
I = 2.16, 1 x FS (w/ H.110)
L = PCIe (1 SS, 1 x type1, 2 x type2)
U = PCIe (1 SS, 1 x type1, 2 x type2, 2 cPCI)
X = No BP installed
Z = Custom

 BP Connector

A = P1 & P2 S; No P3,P4, P5
B = P1 S, P2 L; No P3,P4, P5
C = P1, P2 & P4 S; P3 & P5 L
D = P1 & P2 S; P3, P4, P5 L
E = P1 S; P2, P3, P4, P5 L
F = P1 & P4 S; P2, P3, P5 L
G = P1 & P2 S; P3 L, no P4, P5
H = 2 x PC: P1, P2 & P4 S; P3 & P5 L
I = 2 x 47 PIN Power
X = No connectors
Z = Custom

 Drives

1 = 1 X 3.5"
B = 2 x 2.5"
X = Not installed

 Height

3 = 3U

 Width


8 = 84T

 Rear IO


Y = Yes

 Depth


3 = 300
4 = 360

 Card Orientation

H = Horizontal

 PSU Input

C = 90-230VAC (Fixed)
K = 48VDC (Fixed)
R = 28VDC (Fixed)
X = No PSU

 PSU Output

Output (Note: Not all PSU combinations available)
1 = 100-199 (w/o 3.3V)
2 = 200-299 watts (w/o 3.3V)
X = Not installed

 Voltage IO

3 = 3.3V
5 = 5V
X = Not installed